

# GNT | DATASHEET

## CONTROLLER

VERS 2.0

Issued day: Jun 6,2022

info@vis.solutions.  
www.vis.solutions



## INPUT EXTENSION MODULE GNT-EXT-24 INPUT

Product name	GNT-EXT-24IN
Product or component type	I/O expansion module
Supply voltage	12VDC
Digital Input	24 Dry contact input
Digital outputs (Relays)	None
Port	1 x ROOM BUS. 2 x RS485
Terminal block	Pluggable type terminals. Screw type connectors, 1.5mm <sup>2</sup> -2.5mm <sup>2</sup>
Dimensions (W x H x D) mm	105 x 90 x 65 mm
Weight	0.9 Kg. (~)
Operating temperature	-20 to 60°C (-4 to 140° F)
Storage temperature	-30 to 70° C.
Relative humidity	5 to 95% - no condensation
IP degree of protection	IP20
Standards	TCVN
Housing material	Plastic

### **Important Notes.**

- Inner Room bus cable – CAT5 UTP or dedicated Room Bus cable .
- Check and ensure that all connection are correct after installation.
- The current of each channel must not exceed the rated current.
- Digital input- dry contact only

### **Safety Precautions.**

- The installation and commissioning of the device must be carried out by VIS Solutions or the organization designated by VIS.
- The device should be installed with DIN rail in DB box. VIS does not take responsibility for all the consequences caused by installation and wire connection that are not in accordance with this document.
- Please do not privately disassemble the device or replace parts, otherwise it may cause mechanical failure, electric shock, fire or body injury.
- Please resort to our customer service department or designated agencies for maintenance service. The warranty is not applicable for the product fault caused by private disassembly.
- It is not allowed to exceed the range.

Technical Support.

Email: [info@vis.solutions](mailto:info@vis.solutions)

Tel: +84-028-39390141/+84-932414151

<https://www.vis.solutions>

Copyright by Vis Solutions LTD. All rights reserved specifications subject to change without notice.